



Chains and Sprockets for the
PELLET MILL
Industry

ALLIED-LOCKE



www.alliedlocke.com

CHAINS

- Available in Carbon or Stainless Steel
- Chains Stocked in Multiple Locations
- Fast Turnaround for Less Downtime
- Single and Multiple Strands Available

Chain Number	Pitch	Working Load (lbs)	Ultimate Strength (lbs)	Sidebar Height	Sidebar Thickness	Weight per Ft. (lbs)
81X	2.609	3,000	24,800	1.13	0.16	2.4
81XHH	2.609	4,000	45,000	1.25	0.31	4.6
AL88XH	2.609	2,100	30,000	1.13	0.25	4.2
WH78	2.609	3,500	28,700	1.13	0.25	4.0
WH124	4.000	7,350	60,000	1.50	0.38	8.5
WH132	6.050	15,300	100,000	2.00	0.50	13.8
MXS2124	4.000	3,430	44,000	1.50	0.25	4.8
SS131	3.075	4,500	40,000	1.50	0.38	7.4
SS102B	4.000	6,300	40,000	1.50	0.38	6.9
SS150+	6.050	15,100	100,000	2.50	0.50	21.0
142 Standard	142mm	13,000	73,000	51mm	N/A	6.4

Partial listing of standard chains. Dimensions in inches unless otherwise noted.



Sales and Engineering Support Readily Available

ATTACHMENTS



Backing Plate Options

- Multiple Carbon or Stainless Options
- Custom Cuts and Bends for Every Application



CUSTOM
BENDS



CLEANOUT
CUP



CHANNEL



FLAT
BAR



ANGLE



CUSTOM
SHAPES

Flight Options

- White, Green and Black UHMW Stocked
- Other Materials Available on Request
- Custom Bevels and Shapes Available





ALLIED-LOCKE INDUSTRIES, INC.

800.435.7752 - TOLL FREE PHONE


800.462.3130-FAX

info@alliedlocke.com

www.alliedlocke.com



CS187 REV. 01/2026



www.alliedlocke.com